PRO XL

TRAIN LIKE YOU MEAN IT

THE ULTIMATE PERFORMANCE TREADMILL

A step up from the Pro treadmill, the Pro XL is an absolute must for any human performance training center. Designed and engineered with results in mind to handle any challenge thrown its way. The ideal cardio equipment for uphill running with a max elevation of 25% or high speed interval training and overall endurance.





PRO XL

• St 0

| Standard Feature | |
|------------------|--|
| Optional Feature | |

| | PRO XL | PRO XL VIEW | PRO XL INTERACT |
|--|---|---------------------|---------------------|
| Coded/Non-Coded Polar Heart Rate Pick-up | ٠ | ٠ | • |
| ANT+ Heart Rate Pick-up | • | • | • |
| USB Power Supply | • | • | • |
| Touch Grip Heart Rate Pick-up | • | • | • |
| LED Display Board | • | • | • |
| Personal Trainer Display Board | 0 | 0 | 0 |
| 19" LCD HDTV | > | \bigcirc Embedded | |
| Netpulse Touch Screen Entertainment | > | > | \bigcirc Embedded |
| RS 232 Serial Interface | 0 | 0 | NA |
| CSAFE Communication Compatible | • | ٠ | NA |
| Wireless Remote | 0 | 0 | 0 |
| PT Pro Software | 0 | 0 | NA |
| RFID System | 0 | 0 | NA |
| Running Surface Dimensions | 27" W x 88" L (70 x 224 cm) | | |
| User Weight Capacity | Run: 400 lb. / Walk: 800 lb. (4 mph max) | | |
| Belt Type | 77 Individual Slats | | |
| Drive System | 160 Precision Ball Bearings with 18 Roller Guides (4 mm lateral tolerance) | | |
| Running Surface | Vulcanized Rubber (38-43 shore hardness) | | |
| Drive Motor | 2 hp Continuous (5 hp peak) Brushless Servo | | |
| Unit Weight | 675 lb. (Shipping Weight 939 lb.) | | |
| Width | 48" (122 cm) | | |
| Length | 94" (239 cm) | 98"(24 | 49 cm) |
| Height | 70" (178 cm) | 80" (2 | 03 cm) |
| 0-25% Incline | • | | |
| (-3%) - (+22%) Incline | 0 | | |
| 0-15 MPH (0-24 km/h) | • | | |
| 0-16.5 MPH (0-26 km/h) | 0 | | |
| Reverse | 0 | | |
| Power Supply | 208/230 Vac 20 Amp Power Supply **Dedicated Circuit and NEMA 6-20R Outlet Receptacle Required | | |
| Hospital Package Hospital Grade Circuitry Reverse 4 Year All Components Warranty | 0 | | |
| Jump Plate | 0 | | |
| | | | |

Treadmill specifications subject to change without written notice. Warranties outside the U.S. may vary - Please contact your dealer for details.



CONVENIENT USER CONSOLE

- Comfortable handrail control of speed, elevation, and stop
- Multiple LED readouts monitoring speed, incline, distance,
- time, and heart rate
- CSAFE fitness communications compatible
- Fitness tests and programs; 99 custom workout programs



PATENTED SLAT BELT RUNNING SURFACE

- Individual slats with vulcanized rubber surface
- Zero stretch & Zero slip toothed, wire-reinforced lateral belts
- Near frictionless precision ball bearing rail guide

SAFETY & RELIABILITY

- Emergency stop magnet and safety lanyard
- Polar monitor circuitry integrated heart rate monitoring
- Advanced Slat Belt shock absorption
- Life expectancy of running surface 150,000 to 200,000 miles
- Extended warranty and factory renewal program

USER INTERFACE

SPECIFICATIONS